



19" Widescreen LCD 919Pwz



TECHNICAL SPECIFICATIONS

Screen Size	19"
Viewable Image Size	481mm diagonal
Pixel Pitch	0.243x0.243
Display Area	408.24x255.15
Brightness	300cd/m2
Contrast Ratio	10000:1
Response Time	2ms
Viewing Angles	CR(10):170/160;
Scan Frequency	H:30~83KHz V:55~75Hz
Pixel Frequency	135M
Max. Resolution	1680x1050@60Hz
Recommended Resolution	1680x1050@60Hz
Supported Resolutions	640x480@60/72/75Hz, 800x600@60/75Hz, 1024x768@60/75Hz, 1280x1024@60/75Hz, 1440x900@60/75Hz, 1680x1050@60Hz
Display Colours	16.7M
Compatibility	VESA,VGA,SVGA,XGA,SXGA,Mac®
HDCP Compatible	YES
Input Signal	Analog RGB, DVI-D
Input Connector	15-pin D-Sub & 24-pin DVI-D
Power Supply	110~240VAC, 50/60Hz
Power Consumption	On: <37W , Power saving<2W,off<1W
Plug & Play	DDC 1/2B/CI or VESA DDC2B™
User Control	Auto,Eco/down,Vol/up,Menu,Power
OSD Function	Luminance(Brightness, Contrast, Eco Mode,Gamma(1,2,3),DCR); Image Setup(Clock,Phase,H/V position); Color Temperature (Cool, Warm, Normal, sRGB, R,G,B);Color Boost (Full Enhance, Nature Skin, Green Field, Sky Blue, Auto Detect, Demo); Picture Boost (Frame Size, Brightness, Contrast, Hue, Saturation, H/V Position, Bright Frame on/off) ; OSD Setup (H/V position, Timeout, Language,Transparence); Extra(Image Ratio,Input select,DDC-CI,Information, Auto Config); Reset; Exit; Volume
OSD Languages	8 languages
Speakers	1w *2
Safety & Regulations	Cul , FCC, CE, TUV-bauart, TCO03, EPA, , ISO13406-2, Window previum
Wall-Mount	VESA 100mm
Special Features	black / silver
Cabinet colour	4way HA stand , glossy base and stand , O8OSD , I-menu , 2ms RS time, High resolution and contrast ration .
W x H x D (w/ base) mm	439 x 365 x 250 mm
W x H x D (package) mm	491(L)X442(W)X234(H)
Weight	5.75Kg/7.4Kg
Loading Qty: 40"/20"	1080/450

Note: Specifications are subject to change without notice.