



F19s



TECHNICAL SPECIFICATIONS

Model Name	F19s
Cabinet Colour	Black
Pixel / Dot Pitch	0.3(H) × 0.3(V) mm
Display Area	409.8(H) × 230.4(V) mm
VIS	470mm
Brightness	250cd/m ²
Contrast Ratio	10000:1 (DCR)
Response Time	5ms
Viewing Angle H / V	170/160(CR≥10)
Scanning Frequency	H:30~80KHz V:55~75Hz
Pixel Frequency	85.5MHz
Maximum Resolution	1366×768@60Hz
Recommended Resolution	1366×768@60Hz
Display Colours	16.7M
Signal Input	Analogue: 0.7Vp-p(standard), 75 OHM, Positive
Input Connector	Analogue RGB Signal: 15-pin D-sub Male
Power Supply	Universal 100~240VAC, 50/60Hz
Power Consumption	On: 28 Watts (Max.), Standby: < 1 Watt
Plug & Play	VESA DDC/2B, DDC/CI
User Control	Contrast/Left, Eco/Up, DCR/Right, Auto/Down, Power/Menu
OSD Languages	8 Languages
Speaker	No
Regulations	cULus, FCC, CE, Windows Vista, ROHS, EPEAT Silver
Dimensions (Monitor)	445.8 * 334.3 * 79.9 mm
Dimensions (Carton)	508 * 394 * 150 mm
Weight (Net / Gross)	3.7Kg / 4.8 Kg
Loading Qty w/pallet	1806 / 840