

Phoenix Thin Client

[Overview](#)

[Business Benefits](#)

[Specifications](#)

[About Thin Client Computing](#)

Specifications



CPU	VIA C3 667MHz
RAM	128MB
Flash Memory	64MB DOM, FTP support for automatic software upgrades
Resolution	640x480 to 1280x1024 at 256 colors, to 1280x1024 at 16 bit colors with ICA
Refresh Rate	Flicker-Free up to 85Hz
Network Protocols	
10/100 Base T Fast Ethernet	Yes
TCP/IP	Yes
DHCP	Yes
PPPoE	Yes
PPP	Yes
Application Protocols	Microsoft RDP 5.0 & Citrix ICA 6.0 protocols
Serial Port	DB-9 pin male connector x 1
Parallel Port	Bi-directional Centronics compatible DB-25 x 1
Display Port	VGA type video output x 1
USB Ports	USB ports x 2
Audio Ports	Audio Out/In, Microphone In
PS/2	104 key PS/2 keyboard & mouse
Server OS Support	
Microsoft Windows 2000 Server	Yes
Microsoft Windows NT 4.0 Server Terminal Server Edition	Yes
Citrix WinFrame, MetaFrame	Yes
XDM Connection	Yes
Terminal Emulation	Optional
Local Netscape or Mozilla Browsers with Macromedia plug-in & Acrobat plug-in	Optional
Local Java Virtual Machine	Optional
Customized Local Application	Optional
Operating System	Embedded Linux
Multiple Sessions	Support up to 7 simultaneous RDP sessions
Operating Temperature	
Powered on	32 to 104 F (0 to 40 C)
Powered off	-14 to 140 F (-10 to 60 C)
Humidity	20% to 80% non-condensing
Power	85 Watts, Full range auto-sensing 90-264 VAC at 47-63 Hz Wake-on-LAN ready
Height	292 mm
Width	52.7 mm
Depth	230 mm
N.W.	2.08 kg
G.W.	2.80 kg
Power Cord	6 ft